



HOUSING Die-formed heavy gauge steel with high-gloss, baked white enamel finish over rust inhibiting phosphate coat. Full black reveal and hinged louver for easy relamping. Access plate provided with 2 KO's and ground screw.

SHIELDING Low iridescence, anodized, semi-specular aluminum parabolic, nominal 3" deep-cell louver held securely by steel latches. "T" hinges allow access from either side.

ELECTRICAL Fully wired for UNV 120-277V, 50-60Hz operation with thermally protected, automatic resetting Class P, sound rated A ballast as standard unless otherwise

specified. UL listed.

MOUNTING Optional EC515 Earthquake Clip for lay-in TEP grid ceilings. Specify FEP for flange unit or use GCK kit. (See page 150.) Flanged units require field assembly.

TEP and FEP Deep Cell Parabolics are attractive high-efficiency fixtures that produce uniform low brightness in the 60°- 90° zone.

TEP and FEP Series Ordering Information

SERIES	SIZE	LAMPS	LAMP TYPE	AIR HANDLING	CELL CONFIGURATION	LOUVER FINISH	OPTIONS
TEP = Lay-in 3" deep cell, semi-specular	124 = 1 x 4 242 = 2 x 2	2 3	14 = 14W T5 17 = 17W T8	Static (standard) AC = Vented on all sides	8C = 1x4 (1 row of 8) 9C = 2x2 (3 rows of 3)	Semi Specular (standard) W = White	SR = Specular reflector** WR = White reflector**
FEP = Flanged 3" deep cell, semi-specular	244 = 2 x 4	4	24 = 24W T5HO 28 = 28W 48" T5 32U = 32W U6" T8* 32 = 32W T8 40TT = 40W TT 54 = 54W T5HO	AH = Vented on 2' side AS = Vented on 4' side	12C = 2x2 (3 rows of 4) 12C = 2x4 (2 rows of 6) 16C = 2x2 (4 rows of 4) 18C = 2x4 (3 rows of 6) 24C3X8 = 2x4 (3 rows of 8) 24C4X6 = 2x4 (4 rows of 6) 27C = 2x4 (3 rows of 9) 32C = 2x4 (4 rows of 8)	S = Specular	ELS1 = Low Lumens ELS2 = Medium Lumens ELS3 = High Lumens

*For 1 5/8" please specify

BALLAST	SWITCHING	VOLTAGE	OPTIONS	ACCESSORIES
B11 = Electronic T8 B11HP(x) = HPT8* B12 = Electronic T5 B14 = Electronic TT D = Dimming (specify)	For 3 and 4 lamp units Blank = dual ballasts 3L = (1) 3-lamp ballast 4L = (1) 4-lamp ballast For 2 lamp units Blank = single ballast 2/1L = (2) 1-lamp ballasts	UNV = 120-277V 120 = 120V 277 = 277V	L = Lamps Installed (Specify Lamps) (U-lamp and TT lamps not installed) FL4 = 3/8", 6' flex with two #18, one ground and two connectors* FL5 = 3/8", 6' flex with three #18, one ground and two connectors* M = Master; includes 11' intertie and snap-in connector S = Satellite; includes snap-in connector FB = Fast Blow Fuse SB = Slow Blow Fuse BP = Bulk Pack	EC515 = Earthquake Clip GCK (Grid Conversion Kits) GCK 14 = 1' x 4' GCK 22 = 2' x 2' GCK 24 = 2' x 4'

*CEE listed T8; specify (L)ow, (N)ormal, or (H)igh ballast factor. Contact factory for NEMA Premium.

**Contact factory for availability

OPTIONS	ACCESSORIES
L = Lamps Installed (Specify Lamps) (U-lamp and TT lamps not installed) FL4 = 3/8", 6' flex with two #18, one ground and two connectors* FL5 = 3/8", 6' flex with three #18, one ground and two connectors* M = Master; includes 11' intertie and snap-in connector S = Satellite; includes snap-in connector FB = Fast Blow Fuse SB = Slow Blow Fuse BP = Bulk Pack	EC515 = Earthquake Clip GCK (Grid Conversion Kits) GCK 14 = 1' x 4' GCK 22 = 2' x 2' GCK 24 = 2' x 4'

